



REX POWER MAGNETICS

DIVISION OF TRANSFACTOR INDUSTRIES INC.  
65 Basaltic Rd. Concord, ON, L4K 1G4 Canada  
Tel: 905-695-8844, 1-800-387-2840 Fax: 905-695-8855  
www.RexPowerMagnetics.com

## ENERGY EFFICIENT TRANSFORMER

-Single Phase Isolation Transformer  
-ANN Self- Cooled

Purchaser: TBA  
PO#: TBA  
SWO#: TBA  
Qty: TBA

PRELIMINARY DRAWING ONLY

This drawing may NOT truly reflect our Final Design. Any resulting order(s) must be accompanied by, or refer to this drawing and be marked with any proposed changes.

Coils: Aluminum Wound  
 Cat. No.: SA15H-K/Z

kVA: 15  
 Primary: 480 Volts  
 Secondary: 120/240 Volts  
 Primary Taps: 2.5 %  
 -Taps FCAN 2  
 -Taps FCBN 2

Frequency: 60 Hz

Insulation Class: 220° C  
 Temperature Rise: 150° C

BIL: 10 kV

Min. Efficiency: 97.7 %  
 -Calculated @ 35% Loaded

Impedance: 4.5 - 5.5 %  
 Weight: 150 Lbs

Termination	Location	Lug Size
-------------	----------	----------

Primary:	Front	2-14 AWG
Secondary:	Front	2-14 AWG

### Wiring Connection:

#### Primary:

Voltage	% Tap	Connect Lines To:
504	105.0	H5 - H6
492	102.5	H4 - H5
480	100.0	H3 - H4
468	97.5	H2 - H3
456	95.0	H1 - H2

#### Secondary:

Voltage	Interconnect:	Connect Loads To:
240	X2 To X3	X1-X4
120	X1 To X3 X2 To X4	X1-X4
120/240	X2 To X3	X1-X2-X4 ( X2 is a Neutral )

### Standards:



1. CSA Certified  
- File No. LR34493
2. UL Listed  
- File No. E108255

### Standard Features:


1. Anti-Vibration pads installed between the enclosure base and the core & coil assembly
2. Ground lug provided

### Special Features:

1. Transformer meets Efficiency per CSA C802.2-06
2. Transformer meets NEMA TP-1-2002 Efficiency



FRONT VIEW



SIDE VIEW

### CSA Enclosure:

1. Type 2 (NEMA 2)  
- Sprinklerproof when the angle between sprinkler heads and opening in the enclosure does Not exceed 45 degree from the vertical.
2. Indoor Ventilated
3. ASA 61 Grey
4. Floor/Wall Mounting

Prepared by: AP

Approved by: VS

Date: NOV.12, 2008