

REX POWER MAGNETICS


DIVISION OF TRANSFACTOR INDUSTRIES INC.

25 BAYWOOD ROAD, REXDALE, ON., M9V 3Y8 TEL.: (416) 747-7818 FAX: (416) 747-1956

**SPECIFICATION SHEET
AUTO TRANSFORMER
TYPE: ANN-SELF COOLED**

CAT. NO.: RC30HB
KVA: 30
PRIMARY: 480 V
SECONDARY: 208 V
PHASE: 3
Hz: 60

WEIGHT: 200 Lbs
INSULATION CLASS: 220EC
TEMPERATURE RISE: 150EC



Wiring Connection:

Primary:

Volts	Phase
480	3

Connect Lines to:
H1-H2-H3

Secondary:

Volts	Phase
208	3

Connect Loads to:
X1-X2-X3

TERMINATION/LOCATION:

PRIMARY (HV):	2-14 AWG	FRONT
SECONDARY (LV):	2-14 AWG	FRONT

STANDARDS:

- CSA Certified
- UL Listed

COILS: Copper Wound

SPECIAL FEATURES: ANTI-VIBRATION PADS INSTALLED.

CSA Enclosure

- Type 2 (NEMA 2)
- Sprinklerproof when the angle between sprinkler heads and opening in the enclosure does not exceed 45E from the vertical
- Indoor Ventilated
- ASA 61 Grey
- Floor/Wall Mounting

