

REX POWER MAGNETICS

DIVISION OF TRANSFACTOR INDUSTRIES INC.

25 BAYWOOD ROAD, REXDALE, ON., M9V 3Y8 TEL.: (416) 747-7818 FAX: (416) 747-1956

**SPECIFICATION SHEET
AUTO TRANSFORMER
TYPE: ANN-SELF COOLED**


CAT. NO.: RC30JC
KVA: 30
PRIMARY: 600 V
SECONDARY: 240 V
PHASE: 3
Hz: 60

WEIGHT: 220 Lbs
INSULATION CLASS: 220EC
TEMPERATURE RISE: 150EC

TERMINATION/LOCATION:
PRIMARY (HV): 2-14 AWG FRONT
SECONDARY (LV): 2-14 AWG FRONT

STANDARDS:
 -CSA Certified
 -UL Listed

COILS: Copper Wound
SPECIAL FEATURES: ANTI-VIBRATION PADS INSTALLED.



Wiring Connection:

Primary:
 Volts Phase
 600 3

Connect Lines to:
 H1-H2-H3

Secondary:
 Volts Phase
 240 3

Connect Loads to:
 X1-X2-X3

- CSA Enclosure
- Type 2 (NEMA 2)
- Sprinklerproof when the angle between sprinkler heads and opening in the enclosure does not exceed 45E from the vertical
- Indoor Ventilated
- ASA 61 Grey
- Floor/Wall Mounting

