



**REX POWER MAGNETICS**

DIVISION OF TRANSFACTOR INDUSTRIES INC.  
65 Basaltic Rd. Concord, ON, L4K 1G4 Canada  
Tel: 905-695-8844, 1-800-387-2840 Fax: 905-695-8855  
www.RexPowerMagnetics.com

**CONTROL TRANSFORMER**

- DRY TYPE
- ANN Self Cooled

Purchaser: TBA  
 PO#: TBA  
 SWO#: TBA  
 Qty: TBA

**PRELIMINARY DRAWING ONLY**  
 This drawing may NOT truly reflect our Final Design. Any resulting order(s) must be accompanied by, or refer to this drawing and be marked with any proposed changes.

REX's Cat. No.: CS350J-K  
 Customer's P/N: N/A  
 VA Rating: 350  
 Primary: 600 Volts  
 Secondary: 120/240 Volts  
 Frequency: 60 Hz  
 Insulation Class: 130° C  
 Temperature Rise: 80° C  
 Weight: 12.0 Lbs



Termination	Location	Terminals
Primary:	Front	Terminal Blocks
Secondary:	Back	Terminal Blocks

**Wiring Connection:**

Primary:	Secondary:	Interconnect:	Connect Lines To:	Connect Loads To:
600	240	X2 To X3	H1-H2	X1-X4
	120	X1 To X3		X1-X4
		X2 To X4		
	120/240	X2 To X3		X1-X2-X4 ( X2 is a Neutral )

**Standards:**

1. CSA Certified  
- File No. LR34493
2. UL Listed  
- File No. E110286



**Dimensions (Inches):**

- A = 4.50
- B = 4.50
- C = 3.75
- D = 3.75
- E = 3.75

( Mounting Slots: 0.31 X 0.625 )

**Design:**

- Open Construction
- Indoor Application
- Floor/Wall Mounting

Prepared by: AP  
 Approved by: VS  
 Date: MAR.10, 2008